Serial No.: 10/070,011 Filed: July 3, 2002

Page : 2 of 9

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently amended) A hardware-based multithreaded processor comprising:

a plurality of microengines, each of the microengines comprising:

a control store;

controller logic;

context event switching logic; and

an execution box data path including an arithmetic logic unit (ALU) and a general purpose register set, the ALU performing functions in response to instructions, one of the instructions causing the ALU to issue a memory reference to an address in a memory shared among threads executing in the microengines while a context of a thread is <u>waiting inactive</u>.

- 2. (Previously amended) The processor of claim 1 wherein the instruction comprises a command field that sets or clears user-specified bits in a longword.
- 3. (Previously amended) The processor of claim 1 wherein the instruction comprises a command field that reads from the address to a transfer register associated with the microengines.
- 4. (Previously amended) The processor of claim 1 wherein the instruction comprises a command field that locks the memory and then reads the memory.

Serial No.: 10/070,011 Filed: July 3, 2002 Page: 3 of 9

5. (Previously amended) The processor of claim 1 wherein the instruction comprises a command field that writes to the memory from a transfer register associated with the microengines.

- 6. (Previously amended) The processor of claim 1 wherein the instruction comprises a command field that writes to the address and unlocks the address.
- 7. (Previously amended) The processor of claim 1 wherein the instruction comprises a command field that pushes a list element specified by the address onto a specified stack.
- 8. (Previously amended) The processor of claim 1 wherein the instruction comprises a command field that pops a list element specified by the address from a specified stack.
- 9. (Previously amended) The processor of claim 1 further comprising: a transfer register specified as a parameter in the instruction.
- 10. (Previously amended) The processor of claim 1 wherein the instruction further comprises: a first source operand field; and a second source operand field.
- 11. (Previously amended) The processor of claim 10 wherein the first source operand and the second source operand are context-relative registers.
- 12. (Previously amended) The processor of claim 10 wherein the first source operand and the second source operand are 5-bit intermediate data ranging from +31 to 0.
- 13. (Previously amended) The processor of claim 1 further comprising a reference count field specified as a parameter in the instruction.

Serial No.: 10/070,011 Filed : July 3, 2002 Page : 4 of 9

14. (Previously amended) The processor of claim 13 wherein the reference count field specifies a

number of contiguous longwords in the memory to be referenced.

15. (Previously amended) The processor of claim 1 further comprising a queue number as a

parameter in the instruction.

16. (Previously amended) The processor of claim 15 wherein the queue number specifies one of

eight push/pop queues.

17. (Previously amended) The processor of claim 1 further comprising a bit operand as a

parameter in the instruction.

18. (Previously amended) The processor of claim 17 wherein the bit operand sets or clear bits at

an address using a specified bit mask.

19. (Previously amended) The processor of claim 1 further comprising:

an optional token that is set by a programmer in the instruction.

20. (Previously amended) The processor of claim 19 wherein the optional token causes the

instruction to signal a corresponding micro-engine/thread pair that is sourcing or sinking memory

data when complete.

21. (Previously amended) The processor of claim 19 wherein the optional token swaps out a

context of a current thread execution to let another thread context execute.

22. (Previously amended) The processor of claim 19 wherein the optional token swaps out a

current context thread after execution of one instruction.

Serial No.: 10/070,011 Filed: July 3, 2002

Page : 5 of 9

23. (Previously amended) The processor of claim 19 wherein the optional token places a memory

reference into an ordered queue.

24. (Previously amended) The processor of claim 19 wherein the optional token places a memory

reference into a priority queue.

25. (Previously amended) The processor of claim 19 wherein the optional token optimizes

memory bandwidth by placing the memory reference into a read or ordered queue.

26. (Previously amended) The processor of claim 19 wherein the optional token indicates

overriding qualifiers.

27. (Previously amended) The processor of claim 1 wherein the memory is a synchronous

dynamic random access memory (SDRAM).

28. (Previously amended) The processor of claim 1 wherein the memory is a synchronous

random access memory (SRAM).

29. (Previously amended) The processor of claim 1 wherein the memory is a scratch pad

memory.

30. (Currently amended) A method of operating a processor comprising:

issuing a command to a memory shared among threads executing in microprocessors, each

thread having an associated context; and

causing inactivating the context of the thread issuing the command while the command is

executing to wait.

31. (Original) The method of claim 30 wherein the command comprises:

Serial No.: 10/070,011 Filed: July 3, 2002

Page : 6 of 9

setting user-specified bits in a longword.

32. (Original) The method of claim 30 wherein the command comprises: clearing user-specified bits in a longword.

- 33. (Original) The method of claim 30 further comprising: providing an address in the memory to affect a change.
- 34. (Original) The method of claim 33 wherein the command comprises: locking the memory.
- 35. (Original) The method of claim 34 wherein the command further comprises: reading from the address to a transfer register associated with the microprocessors.
- 36. (Original) The method of claim 33 further comprising:
 unlocking the memory; and
 writing to the address from a transfer register associated with the microprocessors.